

Deployment Targets

What

The Targets of a deployment are the endpoints that we'll define for deploying to. Targets allows us to choose individual devices, groups, smart groups and LDAP sources for our deployment. Targets also allows us to avoid deploying to certain devices or groups as well.

When/Why

We'll want to define here the targets and exclusions:

<p>Targets - What you want to receive</p> <p>Groups - Static, Smart Groups, and LDAP OUs to include</p> <p>Devices - Specific devices to include</p>	<div>Targets (3)</div> <div>Groups (1)</div> <table><thead><tr><th>Group Name</th><th>Path</th></tr></thead><tbody><tr><td>HR</td><td>Department/HR</td></tr></tbody></table> <div>Devices (2)</div> <table><thead><tr><th>Name</th><th>Platform</th></tr></thead><tbody><tr><td>Phil - phil@browsers.com</td><td>iOS 13</td></tr><tr><td>Wendy McIlrath</td><td>iOS 13</td></tr></tbody></table>	Group Name	Path	HR	Department/HR	Name	Platform	Phil - phil@browsers.com	iOS 13	Wendy McIlrath	iOS 13
Group Name	Path										
HR	Department/HR										
Name	Platform										
Phil - phil@browsers.com	iOS 13										
Wendy McIlrath	iOS 13										
<p>Exclusions - What you don't want to receive</p> <p>Groups - Static, Smart Groups and LDAP OUs to exclude</p> <p>Devices - Specific devices to exclude</p>	<div>Exclusions (2)</div> <div>Groups (1)</div> <table><thead><tr><th>Group Name</th><th>Path</th></tr></thead><tbody><tr><td>HR</td><td>Department/HR</td></tr></tbody></table> <div>Devices (1)</div> <table><thead><tr><th>Name</th><th>Platform</th></tr></thead><tbody><tr><td>Phil - phil@browsers.com</td><td>iOS 13</td></tr></tbody></table>	Group Name	Path	HR	Department/HR	Name	Platform	Phil - phil@browsers.com	iOS 13		
Group Name	Path										
HR	Department/HR										
Name	Platform										
Phil - phil@browsers.com	iOS 13										

✔ If left blank, the deployment can be saved, but without targets it won't send payloads anywhere. This may be nice for archival purposes.

How

1. From the Targets tab.
2. Select devices you want to get a payload(s). Either groups or individual devices
3. (optional) Select exceptions, groups or devices you do not want to receive any payload(s)
4. Save your work to finish later or next to finish creating your deployment

